



Ceramic Acrylic Paint

Product Data

PRODUCT DESCRIPTION

CERAMIC ACRYLIC PAINT is a high quality, 100% acrylic, insulating ceramic paint. Formulated with ceramic fillers, CAP provides excellent substrate protection along with a uniform, easy to apply, excellent hiding latex finish.

PRODUCT USES

For use on a wide variety of surfaces such as exterior wood, concrete, brick, masonry, stucco and primed metal. Excellent for apartments, condominiums, warehouses, offices residential dwellings and metal structures.

SURFACE PREPARATION

PREVIOUSLY PAINTED SURFACES: Thoroughly clean surface of dirt, oil, grease, chalk or foreign matter by scraping, sanding, scrubbing and/or rinsing. Scrape off any loose, blistering, cracking or peeling paint using a wire brush and scraper. If peeling is extensive, strip, sand and prime the entire surface area. Sand all glossy surfaces before washing. This paint will help resist mildew growth, but will not kill spores, which are nearly invisible and must be removed prior to painting. Scrub soiled, chalky or mildewed surfaces with a solution of one cup detergent, one quart household bleach and one gallon of water. The complete surface to be painted must be cleaned even if it looks clean, because invisible residues may cause peeling. Rinse surface thoroughly. Let dry 24 hours.

WOOD: Prime bare wood with one or two coats of Adhesive Primer Sealer depending on condition of the surface. Sand weathered or discolored wood down to solid wood. Clean free of all dust, then prime. Pressure treated wood must be aged at least 6 months before it can be primed.

METAL: Clean surface of all grease, oil and foreign matter before priming. Rusted metal and galvanized metal must be primed with a metal primer sealer such as APS or Rhino Rust Bond.

MASONRY: Prime masonry before painting. New masonry must either be sealed with APS or aged 60 days before priming.

APPLICATION DATA

Stir well. Thinning is not recommended but if necessary use water sparingly. Do not apply when temperatures are below 40 degrees Fahrenheit or when humidity is very high. Do not apply when paint will be subjected to rain or heavy dew.

Apply using brush, roller or spray. Spread uniformly. Allow at least 4 hours to dry before applying a second coat. Two coats are required for warranty purposes.

CLEAN UP

Clean up all tools, equipment and spills immediately after use, while the product is still wet, with warm soapy water.

TECHNICAL DATA

FINISH	Flat, Satin, Semi-Gloss
COLOR	white
VEHICLE TYPE	Copolymer Emulsion
SOLIDS BY WEIGHT	54% +/- 5%
GALLON WEIGHT	10.8 lbs +/- .6 lbs
SPREAD RATE	200-350 Sq. Ft./Gal.
DRY TO TOUCH	2 to 4 Hours
RECOAT	4 Hours
FULL CURE	5 to 7 Days
SIZES	5 Gallons or 55 Gallons